TelaDrop Drop N Tell Shock Indicator Visually Indicates If a Package Has Been Dropped

The Tela*Drop* Drop N Tell Shock Indicator and included warning labels will alert shippers and handlers to take extra care with your product. Designed to activate at one of six pre-set G-force thresholds, this brightly colored device takes the guesswork out of knowing if fragile shipments were dropped.

The TelaDrop is available in resettable or non-resettable configurations.

See the TelaDrop activation instructions for guidance on activating and mounting the device.

DESCRIPTION

- Resettable or Non-Resettable Impact Indicator
- Bi-directional arrow indicator windows
- Arrow windows turn dark blue after impact
- Rated thresholds; 5, 10, 15, 25, 50, 100G

PACKAGING

• Zip lock bags or boxes

COMPONENTS

- Polystyrene TelaDrop Indicator
- Warning labels card
- Pressure sensitive adhesive back
- Activating pin (non-resettable version only)



SHELF LIFE: Guaranteed 2 years from date of shipment if maintained in a cool (less than 90°F), dry (less than 50% RH) environment.

WARRANTY: The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness of purpose: Sellers and manufacturers only obligation shall be to replace such quantity of the product proved by Telatemp Corporation to be defective.

LIMITATION OF LIABILITY: All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. Telatemp Corporation recommends each user determine the suitability of the products for the intended application. Telatemp Corporation shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

*Prices and specifications are subject to change without notice.



TelaDrop Drop N Tell Shock Indicator Specifications:

Presentation:	Polystyrene Tela <i>Drop</i> Indicator, Carton Warning Label, Bill of Lading Warning Label
Dimensions:	0.83 x 2.02 x 0.21 in. (21 x 51 x 5 mm)
Weight:	0.2 oz. /set (6 g)
Accuracy:	±20% of the rated G-force
Shock Sensor:	Single axes weighted mass leaf spring actuated sensors
G-force Ratings:	5, 10, 15, 25, 50, 100G
Activation:	Bi-directional arrows turn dark blue
Mounting:	Mount vertically to the axis of shock with the self-adhesive back or with 2 no. 6-32 screws (not included). Three units are required for a complete dimensional readout (six directions).
Resettable TelaDrop:	Reset before each use per product instructions. Can be reused up to ten times.
Non-Resettable Tela <i>Drop</i> :	Pull the metal pin on the top of the Tela <i>Drop</i> to activate. It cannot be reset. Exercise care not to trip the device as the pin is being pulled.
Adhesive:	Pressure sensitive polyethylene foam tape with high tack rubber adhesive
Storage:	Cool dry environment

*Prices and specifications are subject to change without notice.