

WATERPROOF pH TESTR 30 WITH TEMPERATURE READOUT

The reliable Waterproof pH Testr 30 is built to work in most outdoor applications such as taking pH measurements in lakes and streams. Featuring integral temperature display, the pH testr 30 has a pH range from -1.00 to 15.00 and temperature range between 0°C to 50°C (32°F to 122°F). The resolution (pH) is 0.01 and accuracy is ± 0.01 .

The design of the pH Testr 30 allows the device to float in water and be retrieved easily when a line is attached to the housing. The special Valox® sensor housing resists most chemicals. The double-junction electrode sensor handles wastewater and solutions containing sulfites, heavy metals, and TRIS. The electrode sensor comes with a clog-resistant Kynar® junction and a recessed glass pH bulb to protect against breakage.

The keypad clicks to confirm operation and allows access to a variety of functions. Calibrate up to three pH points with the auto buffer recognition at both USA and NIST standard buffers. Additional features include automatic temperature compensation (ATC), hold function, auto-off function, self-diagnostic error messages, and a three-segment battery-life indicator.

FEATURES

- Replaceable sensor
- Replaceable battery
- Temperature Readout
- Waterproof
- User Calibration
- Chemical Resistant
- Easy To Read Display

**APPLICATIONS**

- Laboratory Testing
- Field Testing In All Environments

TO ORDER

- 356-3430 Double Junction Waterproof pH Testr 30
- 356-2438 Replacement pH Double Junction Electrode

WARRANTY: The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness of purpose: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved by Telatemp Corporation to be defective.

LIMITATION OF LIABILITY: All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. Telatemp Corporation recommends each user determine the suitability of the products for the intended application. Telatemp Corporation shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

**Prices and specifications are subject to change without notice.*

CALL TOLL FREE HOTLINE 1-800-321-5160 www.telatemp.com

Telatemp Corporation 351 South Raymond Avenue Fullerton, CA USA 92831-4624
Phone +714-879-2901 Fax +714-870-8136 customerservice@telatemp.com

DOUBLE JUNCTION WATERPROOF pH TESTR 30 SPECIFICATIONS:

Product Type: pH
Meter Style: Tester
Dimensions: 6.5"L x 1.5" Dia.
Range (pH): -1.00 to 15.00
Temperature Range: 32°F to 122°F (0°C to 50°C)
Resolution (pH): 0.01
Accuracy (pH): ±0.01
Temperature compensation: Automatic
Display: LCD
Calibration: 3
Waterproof: Yes
Buffer recognition: USA, NIST
Power: Four 1.5V batteries
CE Compliance: Yes

**Prices and specifications are subject to change without notice.*

CALL TOLL FREE HOTLINE 1-800-321-5160 www.telatemp.com

Telatemp Corporation 351 South Raymond Avenue Fullerton, CA USA 92831-4624
Phone +714-879-2901 Fax +714-870-8136 customerservice@telatemp.com