

**EI-1E-DC-32-L: 2-CHANNEL TEMPERATURE DATA LOGGER WITH INCLUDED RANGE C PROBE**

Featuring a large multi-function LCD display with internal and external temperature sensors, this iLog model will record internal temperature exposure from -40°C to 70°C (-40°F to 158°F) and external temperature exposure from -20°C to 100°C (-4°F to 212°F), with a resolution of 0.1°C (0.1°F).

The iLog Internal/External Temperature Data Logger also features customizable alarm settings, a programmable start function, an internal sensor response time of T90 of 20 minutes and external sensor response time of T90 of 5 minutes in moving air. Up to 32,000 samples (16,000 samples per sensor) can be recorded to memory for downloading to your PC. The user programmable sampling frequency can be set from 1 second to 10 days.

Relevant applications include; Refrigerators/Freezers, Commercial Refrigeration Systems, Wine Storage, Medical Storage Facilities, Greenhouses, Florists, Museums, and Laboratories.

With the Escort Console Software\*, starting, stopping and downloading from the iLog Internal/External Temperature Data Logger is simple and easy. Data can be viewed in graphical or text formats, displayed in °C, or °F and saved to your PC as an electronic file. The data can also be opened in Excel® for further calculations.

Complete user manual can be viewed onscreen, saved to your PC or printed out from the software.

\*EA-SWP-USB Software & USB Interface Dock is required.

**FEATURES**

- Large LCD display with multi function viewing
- Bookmark readings via a simple magnet swipe
- 0.1°C resolution provides an informative advantage
- Provides maximum data logging reliability and accuracy
- Customizable alarm settings and programmable start function
- User-friendly multi-language software for easy programming and download

**BENEFITS**

- View data in graph or text formats
- Moisture & dust intrusion rated IP65
- Displays temperature in °F or °C
- USB Interface Specification

**TO ORDER**

- EI-1E-DC-32-L iLog Internal Range D/External Range C Data Logger
- EA-SWP-USB Software & USB Interface Dock



**WARRANTY:** The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness of purpose: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved by Telatemp Corporation to be defective.

**LIMITATION OF LIABILITY:** All physical properties, statements, and recommendations are either based on tests we believe to be reliable or our experience, but they are not guaranteed. Telatemp Corporation recommends each user determine the suitability of the products for the intended application. Telatemp Corporation shall not be liable for direct, indirect, special, incidental or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability or any other legal theory.

*\*Prices and specifications are subject to change without notice.*

**CALL TOLL FREE HOTLINE 1-800-321-5160 [www.telatemp.com](http://www.telatemp.com)**

Telatemp Corporation 2910-C East La Palma Avenue Anaheim, CA USA 92806  
Phone +714-414-0343 Fax +714-414-0383 [customerservice@telatemp.com](mailto:customerservice@telatemp.com)



## iLog Internal Range D/ External Range C Data Logger

iLog Internal/External Temperature Data Logger EI-1E-DC-32-L

Internal Channel:

Temperature Range: Internal Range D: -40°C to 70°C (-40°F to 158°F)

Accuracy:  $\pm 0.35^{\circ}\text{C}$  from -40°C to 70°C (-40°F to 158°F)

Resolution: 0.1°C (0.1°F)

External Channel:

Temperature Range: External Range C: -20°C to 100°C (-4°F to 212°F)

Accuracy:  $\pm 0.3^{\circ}\text{C}$  -20°C to 0°C,  $\pm 0.25^{\circ}\text{C}$  0°C to 70°C,  $\pm 0.3^{\circ}\text{C}$  70°C to 100°C

Resolution: 0.1°C (0.1°F)

Sensor Response Time:

Internal Sensor: T90 of 20 minutes in moving air

External Sensor: T90 of 5 minutes in moving air

Resolution: 0.1°C (0.1°F)

Liquid Crystal Display: Software programmable - Operating Temp -20°C to 70°C (-4°F to 158°F)

Memory: 32,000 samples (16,000 samples per sensor)

Sampling Frequency: 1 second to 10 days

Time and date: Real time clock, accuracy  $\pm 1$  minute per month at ambient, multiple time zones supported

Security: Password protected (programmable Escort Console software)

Power Source: User replaceable 3.6V 1/2 AA lithium battery

IP Rating: IP65 (when external sensor is connected)

Software: ESCORT Console

Dimensions: 3.0" Dia x ".70" H (80mm x 18mm)

Sensors: 1 Internal & 1 External (Range C probe included)

Probe Dimensions: 1m cable, 80 x 4.5mm stainless steel sheathed tip

Weight: 2.3 oz (68 grams) including battery

Case Material: Polycarbonate

Operating Temperature: -40°C to 85°C (-40°F to 185°F) Note, battery temp and electronics excluding plastic case

Typical Battery Life: 1 to 2 years

Recorder start-up: Via magnet swipe or programmable auto start

Approvals: CE, EN12830

Warranty: 1 year from date of shipment, excluding battery

*\*Prices and specifications are subject to change without notice.*

**CALL TOLL FREE HOTLINE 1-800-321-5160 [www.telatemp.com](http://www.telatemp.com)**

Telatemp Corporation 2910-C East La Palma Avenue Anaheim, CA USA 92806  
Phone +714-414-0343 Fax +714-414-0383 [customerservice@telatemp.com](mailto:customerservice@telatemp.com)